


TECHNICAL **SPECIFICATIONS**

MAX. WORKING GRADIENT	up to 60°
? SPEED	4 mph (LOW SPEED) 6 mph (HIGH SPEED)
ENGINE	KAWASAKI FS730V EFI AIR COOLED - V TWIN
ENGINE POWER	16,6 KW, 23 HP NET POWER GROSS POWER 25,5HP
EMISSIONS REGULATIONS COMPLIANCE	STAGE V & EPA TIER 4 FINAL
ELUEL	PETROL
FUEL TANK CAPACITY	5.6 gal
CUTTING WIDTH	31.5 in
NUMBER OF BLADES	2 MOB DELTA BLADES
CUTTING HEIGH	1 TO 5 in ELECTRONICALLY ADJUSTABLE
DRY WEIGHT	470 kg 1036 lbs
TRACTION DRIVE	H YOROSTATIC TRANSMISSION ELECTRONIC PROPORTIONAL
MOWER DRIVE	2 BELT DRIVE WITH ELECTROMAGNETIC CLUTCH/BRAKE - FAST STOP

























TOWING HITCH



TOUGH UNDERCARRIAGE WITH STEEL ROLLERS, ANTI-**DETRACKING SYSTEM AND GREASE TENSIONER**



TOUGH SWINGING BLADE

HIGH GRASS

NO PROBLEM

BI-DIRECTIONAL CUTTING

OTE-CONTROLLED







CUTTING HEIGHT ELECTRONICALLY ADJUSTABLE









DRIVING IS EXTREMELY EASY AND PRECISE SINCE THE ADVANCEMENT AND STEERING OF THE TRACKS TAKE PLACE THROUGH A SINGLE JOYSTICK, LEAVING THE OTHER HAND FREE FOR ALL THE **OTHER FUNCTIONS OF THE REMOTE CONTROL.**

